



BASIC INSTALLATION SHEET

STEP 1: Open the installation pack, check to make sure you have everything listed to the left needed for your installation.

STEP 2: Decide if your install will be on a wall or will be a hanging install.

STEP 3: If you are doing a hanging install skip this step and go onto step 4. Your sign has mounting holes, mark holes on wall. For drywall or concrete walls Drill holes and insert the nylon anchors. For wood or metal walls just screw in place with the 4 #10 1.5" screws. We recommend using the 1/2" spacers between the wall and the sign panel (See photo A).

STEP 4: Hanging installation, Measure the distance between the two top holes of the sign. Place the two D Rings at those measurements using the 4 #8 X 1/2" Screws.(See Photo B) Install the 2 S hooks into the holes at the top of the sign panel. Install the 2 hanging cables. The eye end attaches to the s hook. The clasp end goes to the D rings. (See Photo C) Adjust the height of the sign by holding the hosing and pulling the cable through. After you have the correct height cut the excess cable off. (See Photo D) To release the cable push in on the bottom where the cable go's in and that will release the cable.(See Photo E)

STEP 5: Install the power supply preferable above the sign on a solid surface. Clean the area the power supply will be placed the power supply has Velcro applied install in place. See Photo F



PHOTO A



PHOTO B



PHOTO C



PHOTO D



PHOTO E



PHOTO F